



**MULTIPLES OF SENSOR AMPERE RATING**

<p><b>GENERAL ELECTRIC</b></p> <p><b>Sensor Rating (Amperes)</b> 200, 400, 600, 800, 1000, 1200, 1600, 2000 amperes</p> <p><b>Voltage Rating</b> 600 volts ac</p> <p><b>Frequency Rating</b> 50/60 Hertz</p>	<p><b>INSULATED CASE CIRCUIT BREAKER</b> <b>POWER BREAK<sup>®</sup></b> Solid State</p> <p>With <b>VersaTrip<sup>®</sup></b> MOD2</p> <p><b>Types TPSS, THSS Ground Fault Pickup</b> <b>Settings and Delay Time-current Curves</b> <small>(Curves apply at 50/60 Hertz and from -20C to +55C breaker ambient)</small></p>	<p><b>GES-6189</b></p> <p><b>Adjustments</b> Ground-Fault Units: Pick-up current settings are 0.3X, 0.4X, 0.5X, 0.6X, 0.7X and 0.75X for 200 to 1600A sensor ratings, and 0.2X, 0.25X, 0.3X, 0.4X, 0.5X and 0.6X for 2000A sensor ratings. Time-delay bands are maximum, intermediate, and minimum.</p>
--	---	---