



<p><b>GENERAL ELECTRIC</b></p> <p>Sensor Rating (Amperes) 150, 200, 300, 400, 500, 600, 800, 1000, 1200, 1600, 2000, 2500 amperes</p> <p>Voltage Rating 600 volts a-c</p> <p>Frequency Rating 60 Hertz</p>	<p><b>MOLDED CASE CIRCUIT BREAKER</b></p> <p>Solid State</p> <p><b>VersaTrip™</b></p> <p>Types TJS, TKS, TPSS &amp; THSS</p> <p><b>Ground Fault Pick-up Settings and Delay Time-current Curves</b></p> <p><small>(Curves apply at 60 Hertz and from -20°C to +55°C ambient)</small></p>	<p><b>GES-6134</b></p> <p><b>Adjustments</b></p> <p>Ground Fault Units: Pick-up current settings are 0.3x, 0.4x, 0.5x, 0.6x, and 0.7x for 150 to 1600A sensor ratings, and 0.25x, 0.3x, 0.35x, 0.4x, and 0.45x for 2000 to 2500A sensor ratings. Time-delay bands are maximum, intermediate, and minimum.</p>
--	---	---

3-73 (5M)

GENERAL ELECTRIC CO., CIRCUIT PROTECTIVE DEVICES PRODUCT DEPT., PLAINVILLE, CONN.

K215-126