



<p>GENERAL ELECTRIC</p> <p>Ground-trip Settings (Amperes)</p> <table style="width: 100%; border: none;"> <tr> <td style="border: none;">AK-25</td> <td style="border: none;">100, 200, 300, 400</td> </tr> <tr> <td style="border: none;">AK-25 & -50</td> <td style="border: none;">300, 600, 900, 1200</td> </tr> <tr> <td style="border: none;">AK-75 & -100</td> <td style="border: none;">750, 1500, 2250, 3000</td> </tr> </table> <p><small>1 Trade-mark of General Electric Company</small></p>	AK-25	100, 200, 300, 400	AK-25 & -50	300, 600, 900, 1200	AK-75 & -100	750, 1500, 2250, 3000	<p>TYPE AK LOW-VOLTAGE POWER CIRCUIT BREAKER</p> <p>POWER SENSOR¹ SOLID-STATE GROUND-TRIP DEVICE</p> <p>Type PS-1A Ground Trip</p> <p>Time-current Curves</p> <p><small>(Curves apply at 60 Hertz and from -20 C to +55 C ambient)</small></p>	<p>GES-6031</p> <p>Adjustments</p> <p><small>Short-time-delay Unit: Time settings are 0.06, 0.12, 0.18, 0.24, and 0.30 seconds.</small></p>
AK-25	100, 200, 300, 400							
AK-25 & -50	300, 600, 900, 1200							
AK-75 & -100	750, 1500, 2250, 3000							