



<p>GENERAL ELECTRIC</p> <p>Standard Pick-up Ratings (Amperes) 100, 200, 280, 400, 560, 800, 1120</p> <p>Frequency Rating 60 Hertz</p>	<p>TWO-CYCLE POWER-CLASS RECLOSER PHASE TRIP "F" CONTROL</p> <p>Clearing Time-current Curves at 25 C Ambient</p> <p>PICK-UP tolerance is plus or minus (±) 10%. F TIME DELAY is an average curve with plus or minus (±) 10% time tolerance for times above 0.1 seconds. F1, F2 and F3 INSTANTANEOUS curves are maximum curves. Minimum curves are 25% lower in time for times above 0.1 seconds and include allowance for current asymmetry.</p>	<p>GES-6424A</p> <p><small>NOTE: Selection of phase curve also determines the ground curve when the ground-trip accessory is specified. For example, if F2 phase curve is selected, FG2 would be the ground curve. (See GES-6425A for ground curve characteristics.)</small></p>
------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------